Immediate Pret, Inc. ITIMENT: HONDA GOLDWING/GOLDWING TOUR 2018-NEWER Vacadabi CMM ALLEN WERKH SMM ALLEN WERKH SMM ALLEN WERKH 2MM ALLEN WERKH <	BIG BIKE PARTS [®]		INSTALLATION INSTRUCTIONS			
47202013 FITMENT: ENDA GOLDWING/GOLDWING TOUR 2018-NEWER 10005 NEEDED: DMM ALLEN WERNCH: SMM ALLEN WERNCH:	instruction sheet may be reproduced without the written		PART NO. 21-355	R N	MINI BOARD HIGHWAY MOUNT	
TOOLS NEEDED: T/16" WRINCH SMM ALLEN WERKCH AMM AND AM		Parts, Inc.	FITMENT: HO	NDA GOLDWING/G	OLDWING TOUR 2018	-NEWER
Type: WIRKING MMM ALLEN WIRKING 14/4 ALLEN WIRKING REMOVABLE THREAD LOCK PLACE READ TROUGHT AND UNDESTAIND THESE INSTICTIONS BEFORE BEGINNING. "USE REMOVABLE THREAD LOCK ALLEN ASTREMES" STARTING ON THE LEFT SIDE OF THE BIKE, REMOVE THE TWO SCREWS IN HIG. 1. PULL FORWARD ON THE LEFT FOG LIGHT COVER TO REMOVE 9. STARTING ON THE LEFT SIDE OF THE BIKE, REMOVE THE TWO ALEN SCREWS IN HIEL 1. PULL FORWARD ON THE LEFT FOG LIGHT COVER TO REMOVE 9. VIGE A SMM ALEN WIRKING TO REMOVE THE TWO ALEN SCREWS IN HIEL 1. DURE COVEL TAB FROM THE LOWER SHROUD. 9. RILLAS THE RELIGINATION COVER COVEL TO RELASE THE LEFT LOWER COVEL TAB FROM THE LOWER SHROUD. 9. RILLAS THE RELIGINATION COVER THE LIFT LOWER COVEL AND SLIDE IT FORWARD AND DUT TO RELEASE THE TAB HOLDING FRONT OF THE LOWER COVEL AND SLIDE IT FORWARD AND ADD TOT THE LOWER COVEL AND SLIDE IT FORWARD COVER COVER AND SLIDE TH FORWARD COVER. COVER WOLL ON START TAB AND REACTION AND DUT TO RELEASE THE TAB HOLDING FRONT OF THE LEFT LOWER COVEL AND PLACE TO A ADD SCREATCHING. 9. REMOVE THE TWO COULS FROM THE LEFT LOWER COVEL AND SLIDE OF THE LEFT LOWER COVEL COVEL AND SLIDE OF THE LEFT LOWER COVEL A		6MM ALLEN WRENCH	5MM ALLEN WRENCH	4MM ALLEN WRENCH	3MM ALLEN WRENCH	2MM ALLEN WRENCH
<section-header></section-header>	TOOLS NEEDED:	7/16" WRENCH	8MM ALLEN WRENCH	1/4" ALLEN WRENCH	REMOVABLE THREAD LOCK	
 INSTALLATION: I STARTING ON THE LEFT SDE OF THE BIKE, REMOVE THE TWO SCREWS IN THE LEFT LOWER COWL [HG, 2]. USE A SMM ALLEN WERNCH TO REMOVE THE TWO ALLEN SCREWS IN THE LEFT LOWER COWL [HG, 2]. I WILL BACK SLIGHTLY ON THE REAR OF THE LEFT LOWER COWL TO RELEASE IT. USING HG, 3 AND BHG, 5 TOR REFERENCE, CARFUTLURS THE LEFT LOWER COWL (HG, 4]. SLIGHTLY PULL OUT ON THE BACK AND BOTTOM OF THE LEFT LOWER COWL (HG, 4]. SLIGHTLY PULL OUT ON THE BACK AND BOTTOM OF THE LEFT LOWER COWL (HG, 4]. SLIGHTLY PULL OUT ON THE BACK AND BOTTOM OF THE LEFT LOWER COWL AND SLIDE IT FORWARD AND OUT TO RELEASE THE TAB HOLDING. RENADSE THE RUBBER GROMMET IN THE CANTER OF THE LEFT LOWER COWL, AND SLIDE IT FORWARD AND OUT TO RELEASE THE TAB HOLDING. RENOWE THE TWO CLUBS FROM THE EXCINE GUARD COVER, MG, 5 SHOWNS INSIDE OF THE LEFT LOWER COWL LIDE WILL NOT BE REUSED. RENOWE THE TWO CLUBS FROM THE EXCINE GUARD COVER, MG, 5 SHOWNS INSIDE OF THE LEFT LOWER COWL AND AUT TO REIRUSED. REFERENCE THE STIDE THE LOWER COWL TO RELEASE THEM AND REMOVE THE ENSINE GUARD COVER. COVER WILL NOT BE REUSED. REFERENCE THE STIDE THE LOWER COWL TO RELEASE THEM AND REMOVE THE ENSINE GUARD COVER. COVER WILL NOT BE REUSED. REFERENCE THE STIDE THE LOWER COWL TO RELEASE THEM AND REMOVE THE ENSINE GUARD COVER. COVER WILL NOT BE REUSED. REFERENCE THE STIDE THE LOWER COWL TO RELEASE THEM AND REMOVE THE ENSINE GUARD COVER. COVER WILL NOT BE REUSED. REFERENCE TO INSTALL THE CAMP TORS ON THE ENSINE GUARD COVER. THE SINE GUARD COVER. COVER WILL NOT BE REUSED. REFERENCE THE ROWE IN REVERSE ORDER. REFERENCE THE RIGHT SIDE OF THE BIKE. REFERENCE THE RIGHT SIDE THE LOWER COWL TO				EGINNING. *USE REMOVABL	E THREAD LOCK ON ALL FASTENE	RS*
<list-item><list-item><list-item><list-item><list-item></list-item></list-item></list-item></list-item></list-item>						
<list-item><list-item></list-item></list-item>		. STARTING ON THE LEFT S	IDE OF THE BIKE, REMOVE THE	TWO SCREWS IN FIG. 1 . PULI	FORWARD ON THE LEFT FOG LIG	HT COVER TO REMOVE IT.
<list-item><list-item><list-item><list-item><list-item><list-item></list-item></list-item></list-item></list-item></list-item></list-item>	2	USE A 5MM ALLEN WREN	ICH TO REMOVE THE TWO ALLE	IN SCREWS IN THE LEFT LOW	ER COWL (FIG. 2).	
<list-item><list-item><list-item></list-item></list-item></list-item>	3	• PULL BACK SLIGHTLY ON	THE REAR OF THE LEFT LOWER	COWL TO RELEASE IT.		
<list-item><list-item><list-item><list-item><list-item><list-item><list-item></list-item></list-item></list-item></list-item></list-item></list-item></list-item>						D.
<list-item><list-item><list-item><list-item><list-item><list-item></list-item></list-item></list-item></list-item></list-item></list-item>				. ,		
<list-item><list-item><list-item><list-item><list-item><list-item></list-item></list-item></list-item></list-item></list-item></list-item>	6					
<list-item><list-item><list-item><list-item><list-item><list-item></list-item></list-item></list-item></list-item></list-item></list-item>	7					
<list-item><list-item><list-item><list-item><list-item></list-item></list-item></list-item></list-item></list-item>					,	
<text></text>	9					
<text><text><complex-block></complex-block></text></text>	1	0. REPEAT STEPS 1 THROUG	H 6 IN REVERSE ORDER.			
<section-header><section-header><complex-block></complex-block></section-header></section-header>	1				,	
<complex-block></complex-block>	1		-	AND. / ONCE IT IS IN TEACE, IT	GITTEN ALL DOLTS, AND THE SET	
LEFT SIDE OF BIKE	T	NO NO	LIGH COVE	LEFT LOWER	REMOVE TWO 5MM ALLEN SCREWS	FIG. 2
FIG. 3 FIG. 4		LEFT LOWER COWL	R AB LOWER SHROUD		O RELEASE	FIG. 4

