

BIG BIKE PARTS

INSTALLATION INSTRUCTIONS

Copyright2005 by Big Bike Parts, Inc. No part of this instruction sheet may be reproduced without the written permission of Big Bike Parts Inc.

ABS CHROME SIDE FITS KAWASAKI
COVERS VN2000
PART NO. 71-117

TOOLS REQUIRED: PHILLIPS SCREW DRIVER NEEDLE NOSE PLIERS
ADJUSTABLE WRENCH 8MM SOCKET WRENCH

INSTALLATION:

LEFT SIDE INSTALLATION:

1. USE IGNITION KEY TO UNLOCK COVER, THEN PULL FROM BOTH FRONT AND BACK SIDES TO REMOVE FROM BIKE.
2. THE LOCK WILL NEED TO BE REMOVED AND INSTALLED ON THE NEW COVER, SO USING A NEEDLE NOSE PLIERS OR ADJUSTABLE WRENCH, REMOVE THE RETAINING NUT ON THE BACK OF THE OEM COVER AND PULL LOCK OUT.
3. PLACE LOCK IN NEW COVER WITH THE WHITE DOT FACING UPWARD AND FASTEN DOWN USING RETAINING NUT AND TIGHTEN WITH NEEDLE NOSE PLIERS OR ADJUSTABLE WRENCH.
4. THERE IS ALSO A METAL LOCKING TAB THAT NEEDS TO BE REMOVED AND PUT ON THE NEW COVER, USING A PHILLIPS SCREWDRIVER, REMOVE LOCKING TAB FROM OEM COVER AND SCREW INTO NEW COVER USING EXISTING SCREWS.
5. LOCATE THE 2 RUBBER GROMMETS IN THE INSIDE OF THE OEM SIDE COVER, REMOVE THEM AND INSTALL THEM IN THE NEW COVER.
6. WITH THE HARDWARE SWAPPED OUT, YOU ARE READY TO PUT THE NEW COVER ON THE WAY IT WAS REMOVED AND LOCK INTO PLACE, **BUT NOT UNTIL THE RIGHT SIDE HAS BEEN INSTALLED.**

RIGHT SIDE COVER INSTALLATION:

1. WITH THE LEFT COVER REMOVED, PULL THE PASSENGER SEAT RELEASE CABLE TO REMOVE THE PASSENGER SEAT.
2. REMOVE THE DRIVER SEAT BY REMOVING THE TWO BOLTS ON THE REAR OF THE SEAT WITH AN 8MM SOCKET WRENCH.
3. WITH THE DRIVER SEAT REMOVED, LOCATE THE SCREW HOLDING THE RIGHT SIDE COVER ON AND REMOVE WITH A PHILLIPS SCREWDRIVER.
4. PULL THE COVER OFF AND SWAP THE 2 RUBBER GROMMETS AND THE RUBBER WELL NUT FROM THE OEM COVER TO THE NEW COVER.
5. REINSTALL THE NEW COVER THE WAY THE OLD COVER WAS REMOVED.
6. PUT THE DRIVER AND PASSENGER SEATS BACK ON.
7. PUT THE NEW LEFT SIDE COVER ON THE WAY THE OEM SIDE COVER CAME OFF.